



***Perfect compatibility
with Smart phone,
Tablet, and PDA
Advanced concept
RFID Bluetooth reader.***



AT288N

Library, Logistics, Military, etc.

Series Highlights:

- ARM7 Core
- Memory 64KB RAM / 256KB ROM, Ext 8Mb
- RFID UHF EPC Gen2, ISO/IEC 18000-6C / 6B (Option)
- Bluetooth Class 4.1 Classic (HID/ SPP), BLE (Option)
- Cradle
- USB

Tel: +82-70-7012-1317

www.alienasia.com | support@alienasia.com

| AlienTechnology Asia YouTube



AT288N Specification

PERFORMANCE CHARACTERISTICS

Processor	ARM7 Core
Memory	64KB RAM / 256KB ROM, Ext.8Mb

PHYSICAL CHARACTERISTICS

Dimensions (W x L x H)	53.5 (61) x 105.6 x 23.2 (60.3) mm
Weight	180g (with battery)
Display	LED Indicator
Power	3.7V 2,200mAh Lithium - Ion Battery (Rechargeable) Input AC100V ~ 240V / Output DC 5V 2A Power Adapter

Standard I/O Port	Bluetooth, USB Client
-------------------	-----------------------

Audio	Buzzer
-------	--------

DATA CAPTURE

RFID (UHF)	Frequency : CE 865MHz ~ 868MHz FCC 902MHz ~ 928MHz Reading range : 0M ~ 3M (According to Tag & Environment) Writing range : 0M ~ 0.5M (According to Tag & Environment) RF output : 1W Protocol : EPC Gen2, ISO / IEC 18000-6C / 6B (Option) Special function : Anti - Collision
------------	---

WIRELESS COMMUNICATION

Bluetooth	Bluetooth Class 4.1 Classic (HID / SPP), BLE (Option)
-----------	---

USER ENVIRONMENT

Operating temperature	-10°C to 45°C
Storage temperature	-30°C to 70°C
Humidity	95% non - condensing
Drop Specification	1.5M Drop to concrete
Dust & Water Proof	IP65

ADDITIONAL FEATURES

Notification	LED, Buzzer
--------------	-------------

CRADLE

Standard Interface	Mini USB Client / DC Power jack / Extra Battery Charger
--------------------	---

* All Features and specifications described are subject to change without notice.


ACCESSORIES



Adapter
AC Cable



USB Cable



Handstrap

OPTION



Cradle

