

HUMMING BIRD

Folder Type UHF Reader



HUMMING BIRD Folder Type UHF Reader Specifications

CPU	ARM7 Core	Operating temp.	-10 °C to 45 °C
Memory	64KB RAM / 256KB ROM, Ext.8Mb	Storage temp.	-30 °C to 70 °C
Dimension	60 (W) x 90 (L) x 16 (H) mm	Humidity	0% to 95% relative humidity (non-condensing)
Weight	99g (with Battery & UHF)	Drop	1.2M drop to steel
Display	LCD & LED Indicator	Sealing	IP65
Power	1,100mAh Li-Ion battery (Rechargeable) Input AC100V ~ 240V Output DC 5V 2A Power Adapter	Notification	LED Indicator Buzzer, LCD, Vibrator
Standard I/O Port	Bluetooth, USB Client	Accessories	Sync Cable
Audio	Buzzer		
UHF Frequency	CE 865~868 MHz FCC 902~928 MHz		
Reading range	0M ~ 7M(According to Tag & Environment)		
Writing range	0M ~ 0.5M (According to Tag & Environment)		
RF output	26dBm (MAX)		
UHF Engine	WissenMeer developed		
Protocols supported	EPC Gen2 ISO / IEC 18000-6C		
Special function	Anti-Collision		