

AT907

Industry Mobile UHF Reader



- GEN2, ISO / IEC 18000-6C / 6B (Option)
- 5.5" HD Display, Dual Camera (5MP / 13MP)
- 2D Barcode Imager(1D/2D)
- Wi-Fi, Bluetooth, GPS



Long range



Long BAT life



Waterproof



Barcode



Operating temp.

SPECIFICATION

PERFORMANCE SPECIFICATIONS

CPU	Octa-core 2.0GHz
OS	Android 10
Memory	4GB RAM/64GB ROM

PHYSICAL SPECIFICATIONS

Dimension	170 x 103 x 150 mm
Weight	650g
Display	5.5", IPS HD (720 x 1440)
Power	9,000mAh
USB Interface	1 USB Type-C
Standard I/O Port	BT / BLE, USB Client, WLAN
Voice & Audio	LED Indicator, Speaker, Vibrator

USER ENVIRONMENT

Operating temp.	-20°C to 50°C
Storage temp.	-20°C to 70°C
Charging temp.	0°C to 45°C
Humidity	5% to 95% (non-condensing, +25°C)
Drop	1.5M drop
Sealing	IP65

WIRELESS COMMUNICATION

WAN for	2G : GSM/GPRS/EDGE
Data Communication	(850/900/1800/1900MHz)
	3G : WCDMA (850/1900/2100MHz)
	4G : TD-LTE Band 38/39/40/41, FDD-LTE Band 1, 2, 3, 4, 7, 17, 20
GPS	GPS, Tolerance ±5m
WLAN	802.11 a/b/g/n/ac 2.4GHz/5GHz
Bluetooth	BLE V4.2

DATA CAPTURE

Barcode Scan	1D or 2D Imager barcode scanner
Camera	5MP Front, 13MP Rear
UHF Frequency	FCC 902~928 MHz EU 865~868 MHz Korea 917~921 MHz Japan 916~921 MHz (1W) 916~924 MHz (0.25W)
Protocols supported	EPC Gen2 ISO 18000-6C
Reading range	Upto 10 M (Depending on environment & tag type)
Reading rate	Upto 5 M
RF Output	1W

* Product specifications and design are subject to change without notice.
(Product Development In Process)

ACCESSORIES



Adaptor AC Cable



USB Cable



Hand Strap



Alien Technology Asia – Korea
#909, 99, Digital-ro 9-gill Gumcheon-gu Seoul, 08510 Korea
Tel: +82-70-7012-1317 Fax: +82-2-868-1710
www.alienasia.com support@alienasia.com