

ATD100B

Tabletop Bluetooth Reader



- Simple USB interface provides both power and communications
- Programmable RF power control
- Visual indication of reading
- Integrated circularly polarized antenna
- Small footprint enclosure :
157(Length) x 140(Width) x 30(Height) mm
- Bluetooth Class 4.1 Classic



Tabletop



Power supply



RF control



LED indicator



BT 4.1

FEATURES

PHYSICAL SPECIFICATIONS

Dimension	157(L) x 140(W) x 30(H) mm
Weight	200 g
Power and data	Micro USB (1,100mAH Battery included)
Enclosure Material	ABS

DATA CAPTURE

UHF Frequency	CE 865 ~ 960MHz FCC 902 ~ 928MHz
RF output power	Max 20dbm (step 1dB)
Read range	Upto 50cm (depending on Tag)
Antenna	Circularly Polarised

USER ENVIRONMENT

Operating Temp.	-10°C to 50°C
Humidity	Upto 90% relative humidity (non-condensing)

ADDITIONAL FEATURES

Notification	LED, Buzzer
---------------------	-------------

CONNECTIVITY

Bluetooth	Bluetooth Class 4.1 Classic
Communications	VCP, HID (RS232)

* Product specifications and design are subject to change without notice.
(Product Development In Process)

ACCESSORIES



Gender Block
(USB to RJ 9)



RJ 9 to USB Cable

